



## TECHNICAL DATA

### SUPER Q HIGH GLOSS ACRYLIC EMULSION GOLD PAINT (SQ-888)

#### DESCRIPTION

- Super Q High Gloss Acrylic Emulsion Gold Paint is premium quality made from 100% acrylic based emulsion gold paint. Excellent protection for fungus, algae, peeling, chalking and color fading. It possesses the bright gold color, many sparkle gold powder and the highest gloss of gold paint film. Long lasting of gold powder and the durability of gold paint gloss is the excellent.

#### TYPE

- High Gloss Acrylic –Based gold coating system formulated for the long life gloss, gold paint film sparkle and brightness for all seasons.

#### CHARACTERISTICS

- Excellent alkali and fungus resistance. The highest adhesion power to the unpainted substrates.
- Outstanding Gloss and Sparkle
- Excellent Brightness
- Anti-Bacteria and Anti-mould
- Long lasting gold powder
- Resistance to blistering and peeling.
- Good leveling and easy application.
- Pleasant fragrance.
- Anti-UV and Premium new gloss and sparkle.
- Water resistant and water proofing.

#### USES

- A Premium top coat emulsion paint for the protection and decoration of all external substrates such as- (Pagodas, temples, statues, plasters, asbestos, masonry and concrete walls).

#### COLOUR

- Gold color

#### FINISH

- High Gloss and Sparkle

#### APPLICATION DATA

#### METHODS

- Airless or Conventional Spray, Brush, Roller





## TECHNICAL DATA

### DILUTION

- Use Clean water
- 10-15% by Volume (Dilution is to improve the workability)
- 50-100% by Volume (Dilution is to improve the workability)

### THEORATICAL COVERAGE

- 45-55 sq.M per US.Gal

### Dry Film Thickness

- 30-35 microns

### SURFACE PREPARATION

#### New Surface

Masonry & Concrete : Surface must be dry, clean & free of dirt, dust , grease or wax. Concret must be full cured and Left over 30 days before painting.

Wood : Surface must be dry , clean & free of dirt , grease or wax. Sand properly with sand paper for Maximum adhension.

#### Old Surface

Masonry & Concrete : Mechanical sand off old paint, remove un-desirable & poor adhering to the surface by proper Wire brush and sand paper .

Wood : Surface must be dry, clean & free of dirt, dust , grease or wax. Remove all rust.Old paint with mechanical wire brush. Sand properly with sand paper for maximum adhension.

### DRYING TIME

- Touch Dry (45-60 minutes) (at 25 um Dry Film thickness)
- Hard Dry (4 - 8 hour) (at 25 um Dry Film thickness)

### OVERCOATING TIME

- 4-6 hrs (Depends on the surrounding temperature)

### CLEANING

- Lean all equipment immediately with water after use.

### GENERAL INFORMATION

#### Viscosity

- 114 KU





## TECHNICAL DATA

### Specific Gravity

- 1.10 ± 0.05 kg

### Solid Content

- 50-55%

### Painting System

- SQ – 222 Acrylic Alkali Resisting Emulsion Gold Primer
- SQ High Gloss Acrylic Emulsion Gold Paint(SQ-888)

### Packing

- ¼ gallon, 1 gallon

### Storage

- Store in a tightly sealed container in a cool and dry space.

### Shelf life

- Up to 18 months in a tightly sealed container.

### Precaution

- Avoid direct contact with sensitive skin. Use appropriate protective equipment.

**The above information given is intended to give a description of the product performance under specific test conditions. Nevertheless, we cannot assume any responsibility for the use of it since circumstances under which the products are applied in practice are subjected to many variations. We serve the right to alter the given data without notice.**

